## **32VDC CONTROLLERS & ACCESSORIES**

The BECT620C/820(N) Controllers are specifically for use with CESL810-827 Brushless Tools. One controller (ordered separately) is required per screwdriver.

CE/RoHS/ETL Approved.



| Model<br>Number* | Outlets | Speeds | Tool<br>Connector | Input               | Output   | Dimensions<br>L x W x H (mm) | Weight<br>kg / Ibs | Use only with<br>Screwdriver Models                             |  |
|------------------|---------|--------|-------------------|---------------------|----------|------------------------------|--------------------|---|--|
| BECT620C         | 1       | Hi/Lo  | 6 pin             | 100–240VAC,<br>2.0A | 32/24VDC | 145 x 60 x 35                | 0.25 /<br>0.6      | All 32VDC drivers except<br>CESL823–824(P)F,<br>CESL827B(P)-ESD |  |
| BECT820(N)       | -       |        |                   | 100–240VAC,<br>1.2A | 32/24VDC | 195 x 76 x 56                | 0.45 /<br>1.0      | All 32VDC drivers   |  |

\*Part number with North American cordset — Add suffix 'E' for EU cord, or suffix 'UK' for UK cord.

|  | Accessories<br>Select driver model number on the right,<br>follow column down the chart; X signifies<br>an appropriate accessory.   | CESL810(S)  | CESL811 | CESL812 | CESL823(F) | CESL824(F) | CESL823P(F) | CESL824P(F) | CESL827B-ESD | CESL827BP-ESD |
|--|---|---|---------|---------|------------|------------|-------------|-------------|--------------|---------------|
|  | Image: Torque Lock Sleeve Covers torque adjusting nut to deter tampering (1 included), metal lock sleeves also available (replace 'C' with 'E' in model number for ESD-safe version, or replace with 'M' for metal version) Image: Coversion of the tampering of tampe |   |         |         |            |            |             |             |              |               |
| Non-ESD  | DR80-20133C (Clear, Non-ESD)  | X   | Х       | Х       |            |            |             |             |              |               |
|  | DR80-10134C (Clear, Non-ESD)  |   |         |         | Х          | Х          | Х           | Х           |              |               |
|  | DR80-10131E (ESD-Safe)  |   |         |         |            |            |             |             | X            | Х             |
| Pistol Grip Attachment — reconfigures an in-line screwdriver for horizo<br>(add 'ESD' to end of model number for ESD-safe version) |   |   |         |         |            | stener ins | tallation   |             |              |               |
|  | DR80-PG823/4  |   |         |         | X          | X          |             |             |              |               |
| DR80-PG828/9   | DR80-PG823/4P   |   |         |         |            |            | Х           | Х           |              |               |
|  | Tool Holster — fasten to the edge of a v  | ster — fasten to the edge of a workbench and park the screwdriver when not in use |         |         |            |            |             |             |              |               |
| 57 F   | DR80-10136 (w/ lock sleeve)   |   |         |         | X          | X          | X           | X           | X            | Х             |
|  | DR80-20136 (no lock sleeve)   |   |         |         | X          | X          | Х           | X           |              |               |
|  | DR80-20141  | Х   | Х       | Х       |            |            |             |             |              |               |

DR80-10136

ESD



| 32VDC Cable Model | Length     | Pins | Shielded? | Other Notes                             |
|-------------------|------------|------|-----------|---|
| DR96-66002M       | 2m (6.5')  | 6    | no        | included with each driver               |
| DR96-66003M       | 3m (9.8')  | 6    | no        | —                                       |
| DR96-66003M/C     | 3m (9.8')  | 6    | no        | coiled cable with 0.4m whip ends        |
| DR96-66006M       | 6m (19.6') | 6    | no        | —                                       |
| DR96-832X3MSHA    | 3m (9.8')  | 6    | yes       | included with BECT832(N)-SSO, ECT8-SSOA |
| DR96-832X5MSHA    | 5m (16')   | 6    | yes       | _                                       |
| DR96-832X10MSHA   | 10m (32')  | 6    | yes       | _                                       |

