

# 40VDC BRUSHLESS CONTROLLERS & ACCESSORIES

There are two standard Hi/Lo Speed Controllers available for the 40VDC Brushless Drivers. The BECT640NHL is used primarily for screwdriver models CESL828-829(P)(F). The high power output model BECT940HL is used for the higher torque 40VDC tools.

CE/RoHS/ETL Approved.

**BECT640HL**  
HI/LO SPEED CONTROLLER



Model Number*	Outlets	Speeds	Tool Connector	Input	Output	Dimensions L x W x H (mm)	Weight kg / lbs	Use only with Screwdriver Models
<b>BECT640NHL</b>	1	Hi/Lo	6 pin	100–240VAC, 6.3A	40/30VDC, 220W	220 x 134 x 85	1.8 / 4	CESL828–829(P)(F), CESPT824–829(F) (Excluding CESPT828F)
<b>BECT940(N)HL</b>					40/30VDC, 360W			CESLT835–875M(PM) CESP835–865, CESLT9

\*Part number with North American cordset — Add suffix 'E' for EU cord, or suffix 'UK' for UK cord.

Accessories	CESL828(F) CESL829		CESL828P(F) CESL829P		CESL828(F)-ESD CESL829-ESD		CESL828P(F)-ESD CESL829P-ESD		CESLT935–955(P)(F)	CESLT835–875(P)M	CESP(T)835–865	CESPT824–829(F)
	Select driver model number on the right, follow column down the chart; X signifies an appropriate accessory.											
<b>Torque Lock Sleeve</b> — covers the torque adjusting nut to deter tampering (*1 included with applicable drivers)												
<b>DR80-20142C (Clear) *</b>	X	X										
<b>DR80-20142E (ESD-safe) *</b>					X	X						
<b>DR80-20142M (Metal)</b>	X	X	X	X					X			
<b>DR80-20230M/L (Metal)</b>												
<b>DR80-20228M (Metal) *</b>										X		
<b>DR80-20229M (Metal)</b>											X	
<b>DR80-20233M (Metal) *</b>												X
<b>Pistol Grip Attachment</b> — reconfigures an in-line screwdriver for horizontal fastener installation (add 'ESD' to end of model number for ESD-safe version)												
<b>DR80-PG828/9</b>	X		X	X								
<b>DR80-PG828/9P</b>		X		X								
<b>Tool Holster</b> — fasten to the edge of a workbench and park the screwdriver when not in use												
<b>DR80-10136</b>	X	X	X	X								
<b>DR80-TH8-9</b>	X	X	X	X	X							
<b>DR80-TH8M</b>										X	X	X



40VDC Cable Model	Length	Pins	Shielded?	Other Notes
<b>DR96-10016M</b>	2m (6.5')	6	no	included with each driver
<b>DR96-10018M</b>	3m (9.8')	6	no	—
<b>DR96-10018M/C</b>	3m (9.8')	6	no	coiled cable with 0.4m whip ends
<b>DR96-10020M</b>	6m (19.6')	6	no	—
<b>DR96-840X3MSHA</b>	3m (9.8')	6	yes	included with BECT840/940-SSO, ECT8-SSOB
<b>DR96-840X5MSHA</b>	5m (16')	6	yes	—
<b>DR96-840X10MSHA</b>	10m (32')	6	yes	—