## **CESL8 40VDC BRUSHLESS SCREWDRIVERS**

Delta Regis 40VDC Premium Brushless Screwdrivers pack the performance to satisfy demanding assembly applications. With brushless motor technology that withstands higher duty cycles, these drivers are ready to perform on production lines typically dependent on pneumatic tools. As with all Delta Regis Shut-off Clutch Screwdrivers, excellent torque repeatability is the fundamental building block that defines these models. A host of screwdriver configurations, accessories and control options are available to make the 40VDC Series an ideal choice for production assembly across a wide range of industries. Fast versions of some screwdrivers are available to speed up production lines that require installation of long fasteners.

- Clean, powerful 40V brushless motor technology
- 1/4" hex drive
- · High speed versions available
- Dependable, long lifespan
- Lever and push start versions available, forward/reverse switch
- · Optional ESD-safe housing available
- CE/RoHS compliant





| Model<br>Number* | Start Type | Torque Range     |           | Speed (rpm)   | Drive    | Length  | Diameter | Weight     |
|------------------|------------|------------------|-----------|---------------|----------|---------|----------|------------|
|                  |            | in-lbs           | Nm        | Speed (Ipili) | Туре     | mm / in | mm / in  | kg / lbs   |
| CESL828S         | Lever      | 8.9–26.0         | 0.98–2.94 | 350           | 1/4" hex | 278     | 39.5     | 0.8 / 1.76 |
| CESL828PS        | Push       |                  |           |               |          |         |          |            |
| CESL828          | Lever      |                  |           | 1000          |          |         |          |            |
| CESL828P         | Push       |                  |           |               |          |         |          |            |
| CESL828F         | Lever      |                  |           | 2000          |          |         |          |            |
| CESL828PF        | Push       |                  |           |               |          |         |          |            |
| CESL829S         | Lever      | - 17.4–43.4<br>- | 1.96–4.90 | 350           |          |         |          |            |
| CESL829PS        | Push       |                  |           |               |          |         |          |            |
| CESL829          | Lever      |                  |           | 1000          |          |         |          |            |
| CESL829P         | Push       |                  |           |               |          |         |          |            |

\*ESD-safe housing available — add suffix '-ESD'

