

HIGH TORQUE PREMIUM BRUSHLESS, SHUT-OFF CLUTCH

18-443 in-lbs (2-50 Nm)

CESLT8_M Series Screwdrivers incorporate an aluminum front collar to facilitate fixture mounting and each driver includes an accessory side handle for handheld applications (Excludes CESLT885/895(P)M Models).

40VDC Series drivers are capable of developing high torques. These drivers must be used with the included side handle attachment or mounted in a torque reaction arm for operator safety.

- Clean, powerful 40V brushless motor technology
- 1/4" hex drive
- Dependable, long lifespan
- Lever and push start versions available, forward/reverse switch
- Optional ESD-safe housing available
- CE/RoHS compliant



Tool Includes



SUSPENSION BAIL

1/4" HEX BITS: PH#3 (x2)

SIDE HANDLE ATTACHMENT
(Excludes CESLT885/895(P)M Models)

6 PIN, 2m TOOL CABLE

3/8" SQUARE DRIVE
ADD SUFFIX '-SQ'

Model Number*	Start Type	Torque Range		Speed (rpm)	Drive Type	Length mm / in	Diameter mm / in	Weight kg / lbs				
		in-lbs	Nm									
CESLT835M	Lever	18-53	2-6	1200	1/4" hex**	297 / 11.7	46.2 / 1.81	1.25 / 2.75				
CESLT835PM	Push											
CESLT845M	Lever	27-79	3-9	900								
CESLT845PM	Push											
CESLT855M	Lever	36-106	4-12	600								
CESLT855PM	Push											
CESLT855FM	Lever			880								
CESLT855PFM	Push											
CESLT865M	Lever	53-159	6-18	370								
CESLT865PM	Push											
CESLT865FM	Lever			600								
CESLT865PFM	Push											
CESLT875M	Lever	71-221	8-25	370								
CESLT875PM	Push											
CESLT885M-SQ***	Lever	106-310	12-35	350					3/8" Square	393 / 15.5	52.7 / 2.07	2.2 / 4.85
CESLT885PM-SQ***	Push											
CESLT895M-SQ***	Lever	177-443	20-50	200								
CESLT895PM-SQ***	Push											

*ESD-safe housing available — add suffix '-ESD'

**3/8" Square Drive Available — add suffix '-SQ'

***not intended for soft joint applications