

# ESB6 CORDLESS SHUT-OFF CLUTCH NUT-RUNNERS

## Angle Type Brushless High Torque Battery Screwdrivers Series

**Torque Range:**  
6–60 Nm (4.4–44.2 ft-lbs)

### Features:

- Precise shut-off clutch provides excellent repeatability and minimizes torque reaction to the operator
- Hi/Lo speed selection switch on nutrunner
- Powerful DC brushless motor
- High performance 18VDC Li-Ion batteries (purchased separately)
- Front facing LED illuminates fastening area when the trigger is pulled
- To conserve battery life, the screwdriver goes into sleep mode when idle for more than 3 seconds
- Includes swivel bail for suspending from tool balancer
- Long service life — Factory tested to 2,000,000 cycles
- Green/Red LEDs and audible indicators alert operator of proper clutch function at shut-off
- Charging station (purchased separately) provides quick recharge time



### Specifications

Model	ESB6-RA7	ESB6-RA12	ESB6-RA15	ESB6-RA30	ESB6-RA45	ESB6-RA60	
Input Voltage	18V						
Torque	2.5-7 Nm 1.8-5.2 ft-lbs	6-12 Nm 4.4-8.8 ft-lbs	8-15 Nm 5.9-11 ft-lbs	12-30 Nm 8.8-22.1 ft-lbs	15-45 Nm 11-33.1 ft-lbs	25-60 Nm 18.4-44.2 ft-lbs	
Repeatable Torque Accuracy	±5%						
Torque Adjustment	Internal Stepless						
Free Speed (RPM) ±10%	Hi	850	550	350	420	200	200
	Lo	550	350	220	270	130	130
Weight (w/o battery)	1.25 kg / 2.6 lbs	1.5 kg / 3.3 lbs	1.85 kg / 4.0 lbs	1.9 kg / 4.2 lbs	2.85 kg / 6.3 lbs		
Length (w/o battery)	400 mm / 15.7 in	415 mm / 16.3 in	440 mm / 17.3 in	450 mm / 17.7 in	530 mm / 20.9 in		
Applicable Battery	ESB-18VL1950B			ESB-18VL1950C		ESB-18VL3900	
Applicable Charge Station	ESB-CHG80/1950B			ESB-CHG80/1950B		ESB-CHG120 / ESB-CHG80/1950B	
Drive Size	1/4" Hex	3/8" Sq   1/4" Hex		3/8" Sq		1/2" Sq	

