

## Quality industrial products & excellent support for over **20** years!

Electric Screwdrivers Cordless Screwdrivers Manual Screwdrivers

**Screw Presenters** 

Torque Measurement

Tool Supports & Balancers

Smart Systems

Accessories





## DR-XTC1

Transducerized Torque Control System 0.05 ~ 18 Nm (0.4 ~ 159 in-lbs)

Take a look!

Want to test it out on your application before you buy!?

Take advantage of our free Test Drive program today!

**Email us to start your Test Drive** 

The DR-XTC1 allows you to be in full control of your entire fastening process.

Easily setup multiple tightening parameters like speed, thread, direction & torque through the controller directly or via PC with deltaOnpoint software installed.

Create multiple jobs for different assembly stages and quickly switch between desired job dynamically.

Tightening data can viewed instantly in the deltaOnpoint software and can also be stored locally on an SD card to avoid data loss due to untimely internet connectivity issues.



Software Included at NO ADDITIONAL COST!

With purchase of DR-XTC1 and appropriate ESL-XTE Series Transducerized Srewdriver

## Multiple screwdriver models available!

Choose the best transducerized DC driver to suit your application...



ESL-XTE3LT

0.05~3 Nm (0.4~26 in-lbs) Max Speed: 980 RPM



**ESL-XTE3** 

0.6~3 Nm (5~26 in-lbs) Max Speed: 1100 RPM



**ESL-XTE3F** 

0.6~3 Nm (5~26 in-lbs) Max Speed: 1600 RPM



**ESL-XTE5** 

1.0~5.0 Nm (9~44 in-lbs) Max Speed: 1100 RPM



**ESL-XTE7** 

1.4~7.0 Nm (12~62 in-lbs) Max Speed: 660 RPM



**ESL-XTE12** 

2.4~12 Nm (21~106 in-lbs) Max Speed: 750 RPM



**ESL-XTE18** 

3.6~18 Nm (31~159 in-lbs) Max Speed: 450 RPM



- Real-time rundown information
- Intuitive visual feedback
- Quickly program and adjust desired parameters
- Data collection & monitoring capabilities
- Snapshot view shows you all rundown parameters at a glance

Contact us today for more information!









## www.deltaregis.com

7370 Commercial Circle Fort Pierce, FL 34951 772.465.4302

